

35mm/50mm Slats - with strings

Inch mm	15 400	19 500	23 600	27 700	31 800	35 900	39 1000	43 1100	47 1200	51 1300	55 1400	
47 1200	34	35	37	43	46	53	58	61	66	71	73	
70 1800	38	43	46	52	56	65	71	76	85	89	93	
94 2400	43	48	54	60	65	73	82	90	99	106	113	
118 3000	54	60	65	72	80	88	97	104	116	123	130	

Inch mm	59 1500	62 1600	66 1700	70 1800	74 1900	78 2000	82 2100	86 2200	90 2300	94 2400	98 2500	102 2600
47 1200	80	88	92	96	105	112	119	125	130	135	141	147
70 1800	99	105	111	119	128	136	147	154	162	172	181	190
94 2400	121	128	133	140	154	168	180	188	196	211	224	238

35mm/50mm Slats - with standard tapes

Inch mm	15 400	19 500	23 600	27 700	31 800	35 900	39 1000	43 1100	47 1200	51 1300	55 1400	
47 1200	44	47	50	57	64	71	77	82	88	96	99	
70 1800	52	56	61	70	76	87	97	101	113	120	124	
94 2400	58	65	71	82	87	98	110	120	133	143	151	
118 3000	72	79	87	97	106	117	130	138	154	164	173	

Inch mm	59 1500	62 1600	66 1700	70 1800	74 1900	78 2000	82 2100	86 2200	90 2300	94 2400	98 2500	102 2600
47 1200	107	116	120	127	141	150	159	167	173	181	189	196
70 1800	133	141	147	159	172	182	196	206	217	230	242	254
94 2400	162	170	179	188	206	225	241	252	261	280	299	319

Controls: TILT LH - LIFT RH

Minimum width - 290mm

Headrail size: 25/35mm Blinds - 40mm deep x 37mm high, 50/63mm Blinds - 60mm deep x 54mm high

Colour fading: the UV protective coating applied on the slat is guaranteed for 1 year from date of production. Beyond that period some deterioration or fading may occur depending on local conditions.
Operating components: Headrails, mech, etc are guaranteed for 1 year from date of production, subject to normal use, general wear and tear.

OTHER COMPONENTS AVAILABLE

Valance side returns - FOC

Top Fix swivel brackets - 70p - Extension brackets - 90p